

## KASO R16 IT Safes



Kaso high-security IT safes have been developed for the increasing demand for physical security for IT hardware and data intrusion and access protection preventing access to unauthorised people.

Kaso IT safes are certified according to ECB-S R16 Guidelines to Grade I against intrusion and manipulation.

IT safes are supplied with removable pull-out 19-inch rack enabling easy installation of server units and cabling. Cabinets are supplied with integrated and active ventilation system, cable and power conduits for the convenient assembly and operation of the server units.

IT safes are supplied as standard with EN 1300 certified key lock (Class B). As an option cabinets could be also supplied with electronic code locks or mechanical code locks, even with multiple locks depending on unique locking requirements.

IT safes doors are locked and protected with four-way movable locking bolt system. Cabinets are also supplied with floor or wall anchoring option preventing unauthorised removal of the cabinet.

**FACTS**

IT safes are certified according to the ECB-S R16 Guidelines to Grade I.

IT safes are supplied with a thermostatically controlled ventilation system and a removable 19-inch server rack for heights 14U and 28U.

Standard locking is EN 1300 certified high-security key lock (Class B). Cabinets could be also supplied with electronic code locks or mechanical code locks, even with multiple locks.



**MODELS**

	PTK E1-320 R16	PTK E1-340 R16
<b>External</b>		
Height (mm)	962	1662
Width (mm)	634	634
Depth (mm)	1450	1450
<b>Internal</b>		
Height (mm)	850	1550
Width (mm)	500	500
Depth (mm)	950	950
Ventilation perforations	4	4
Cabling entries	6	6
Weight (kg)	395	680
Volume (litres)	451	736
Rack height	14U	28U



Kaso Oy, Lyhtytie 2, P.O. Box 27, 00751 Helsinki, Finland, Tel. +358 10 271 3700  
E-mail: sales@kasosafes.com  
www.kasosafes.com

# KASO R16 IT Safes

**LOCKING OPTIONS AND FITTINGS**

**Standard options**

- EN 1300 certified high-security key lock (Class B)
- Right-handed opening
- Four-way locking mechanism
- Six cabling entries (size 60 x 60 mm)
- Four ventilation perforations for active cabinet ventilation
- Depth adjustable pull-out 19-inch server rack:
  - o model PTK E1-320 R16 - height 14U
  - o model PTK E1-340 R16 - height 28U
- Integrated and active ventilation system including thermostatic control of fan speeds
- Prepared for floor anchoring

**Optional features**

- Accessories and connections to external alarm systems
- Digital code lock or mechanical combination lock. Multiple locks.
- Wall anchoring
- Left-handed opening
- Special RAL colour

